

100-18203,-D 28 Volts 250 Amps

PRODUCT SPECIFICATIONS

Part number	100-18203
System Voltage	24V
Rated Output	250A
Output @ 2000 rpm	160A
Ground	Isolated
Mounting	J180 4" Hinge
Rotation	Bidirectional
Temperature limits:	
Low	- 40°C / -40°F
High	110°C / 230°F
High	125°C / 257°F (with fresh air intake)
Speed limits:	
8000 RPM continuous	
9000 RPM intermittent	
Coating	Corrosion-Resistant E-Coated
Weight	46 Lbs / 21 Kg.
Regulator	Remote

ACCESSORIES:

Remote Voltage Regulator # 3500-5025
90° Elbow Pkg. (360° Rotatable) # 46900-1800

RECOMMENDED FOR:


- Utility Vehicles
- Marine, Mining
- Industrial
- Construction




NOTE:

*This DelStar **100-18203** alternator, meets the marine requirements for Ignition Protection on gas or diesel engines of ISO 8846, USCG, stated in Title 33 CFR 183.410, SAE J1171 and International CE Standards.*

PERFORMANCE CURVES




OUTLINE



Dimensions are listed in mm over (in)


CONNECTIONS



100-18203

28 Volts 250 Amps

ELECTRICAL SCHEMATIC



D100-18203 - 151013

CANADA

Dixie Electric Ltd.
517 Basaltic Road
Concord, ON.
Canada L4K 4W8

Tel.: 905-879-0533 800-461-5799
Fax: 905-879-0532
E-Mail: sales@dixie-electric.com
Web Site: www.dixie-electric.com



Setting the Standard

U.S.A.

Dixie Electric Inc.
5600 Pioneer Creek Drive, Suite D
Maple Plain, MN 55359
U.S.A.

Tel.: 763-475-6629 800-478-0608
Fax: 763-475-6635 800-392-8719
E-Mail: mn.sales@dixie-electric.com
Web Site: www.dixie-electric.us